



**Galvanized open body rigging screw to UNI 2018
jaw/jaw type II A UNI 2018 - art. 2018/2A
oval eye/jaw type II C UNI 2018 - art. 2018/2C**



art. 2018/2A

art. 2018/2C

* Reference standard	Norm UNI 2018
* Type of steel	Low carbon steel - class 4
* Design factor (F.O.S.)	5 : 1
* Standard surface finish	Electro galvanized
* Applications	Lifting, suspension and lashing of load in industry and marine
* Warnings	WLL apply for pull along the rigging screw's axe - working temperature -20° to +200° C - please refer to the technical part of rigging screw section for deepening and other warnings
* Remarks	Round eye/jaw type II B UNI 2018 and hook/jaw type II D UNI 2018 available upon request

Technical data														
code		thread M	WLL t ⁽¹⁾	measures mm										approx. weight per pc. kg ⁽²⁾
art. 2018/2A	art. 2018/2C			length l		length c	width w	depth a	dia. p	thickn. s	width b	depth k	dia. d	
				closed	open									
FV20182A10	FV20182C10	10	0,25	252	367	160	12	26	8	6	16	28	8	0,4
FV20182A12	FV20182C12	12	0,4	290	415	180	16	33	10	7	20	35	10	0,65
FV20182A16	FV20182C16	16	0,63	338	473	200	20	38	12	8	25	45	13	1,17
FV20182A20	FV20182C20	20	1	379	509	220	24	42	16	10	25	45	15	2,01
FV20182A22	FV20182C22	22	1,6	430	565	240	28	46	20	12	30	56	19	3,05
FV20182A27	FV20182C27	27	2	463	598	260	32	51	22	14	30	60	19	4,58
FV20182A30	FV20182C30	30	2,5	515	660	280	36	57,5	25	16	36	70	24	6,62
FV20182A33	FV20182C33	33	3,15	512	692	300	40	64	28	18	36	70	24	8,82
FV20182A36	FV20182C36	36	4	568	758	320	45	70	32	20	42	85	29	12
FV20182A39	FV20182C39	39	5	589	794	340	50	76	36	22	42	85	29	15
FV20182A45	FV20182C45	45	6,3	660	880	380	55	82	40	24	48	95	33	21,5
FV20182A52	FV20182C52	52	8	728	968	420	60	89	42	26	55	105	37	29,2
FV20182A56	FV20182C56	56	10	800	1055	460	65	97,5	45	28	60	115	42	38,7
FV20182A64	FV20182C64	64	12,5	895	1165	500	70	110	50	30	66	135	47	53,5
FV20182A72	FV20182C72	72	16	969	1259	540	80	122	56	33	74	150	50	72,2
FV20182A76	FV20182C76	76	20	1052	1362	580	90	133,5	63	36	81	165	58	93,9
FV20182A80	FV20182C80	80	25	1135	1465	620	100	145	70	40	88	180	65	120

⁽¹⁾ metric tons of 1.000 kg ⁽²⁾ weight referring to art. 2018/2A - art. 2018/2C weighs approx. 10% less.
The sizes in bold character are stock-items.