

Drum hook - art. 3770



* Reference standard	Industrial standard
* Type of steel	Alloy steel quenched and tempered
* Design factor	5 : 1
* Surface finish	Red RAL 3001 painted
* Applications	Assembly of sling for drum lifting
* Warnings	To be used in pair - they should be used solely for assembly of drum lifting slings, sliding on chain to form a closed triangle; improper use may result in dangerous situations - please refer to the technical part of fittings section for deepening and other warnings

Dimensional tolerances

The tolerances of forged components according to UNI EN 10243-1 apply

Technical data

code	WLL t*	Dimensions in mm						weight each appr. kg
		eye inside width	eye outside width	overall length	lip height	lip depth	maximu thickness	
VSGF00000	1	37	64	120	59	41	13	0,50
* metric tons of 1.000 kg		The sizes in bold character are stock-items.						

Pipe (sorting) hook - art. 3780



* Reference standard	Industrial standard
* Type of steel	Alloy steel quenched and tempered
* Design factor	5 : 1
* Surface finish	Red RAL 3001 painted
* Technical features	High working load limit with small dimensions
* Applications	Lifting and handling of metallic pipes - grip on pipe's ends
* Warnings	To be used in pair - they should be used solely for pipe lifting; improper use may result in dangerous situations - please refer to the technical part of fittings section for deepening and other warnings

Dimensional tolerances

The tolerances of forged components according to UNI EN 10243-1 apply

Technical data

code	WLL t*		Dimensions in mm					weight each appr. kg
	on throat's bottom	on tip	eye inside width	eye outside width	overall length	max. of throat	min. height of throat	
VSGT00000	7,5	2	35	72	247	67	30	3,03
* metric tons of 1.000 kg		The sizes in bold character are stock-items.						